

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : H04L 1/00, 1/12, H03M 13/00		A1	(11) International Publication Number: WO 00/48353
			(43) International Publication Date: 17 August 2000 (17.08.00)
(21) International Application Number: PCT/US99/02995 (22) International Filing Date: 11 February 1999 (11.02.99) (71) Applicant: HUGHES ELECTRONICS CORPORATION [-/US]; Building 001, M/S A109, 200 N. Sepulveda Boulevard, P.O. Box 956, El Segundo, CA 92045-0956 (US). (72) Inventors: HAMMONS, A., Roger, Jr.; 14074 Saddle River Drive, North Potomac, MD 20878 (US). EROZ, Mustafa; 18425 Lost Knife Circle #101, Montgomery Village, MD 20886 (US). (74) Agent: WHELAN, John, T.; Hughes Electronics Corporation, Building 001, M/S A109, 200 N. Sepulveda Boulevard, P.O. Box 956, El Segundo, CA 90245-0956 (US).			(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report.

(54) Title: OPTIMIZED RATE-COMPATIBLE TURBO ENCODING



UNIVERSAL CONSTITUENT ENCODER
RECOMMENDED FOR FORWARD LINK TURBO
CODES OF VARYING INTERLEAVER DEPTH

(57) Abstract

A method and apparatus for Turbo encoding uses a set of rate-compatible Turbo Codes optimized at high code rates and derived from a universal constituent code. The Turbo Codes have rate-compatible puncturing patterns. The method comprises: encoding a signal at a first and second encoder using a best rate 1/2 constituent code universal with higher code rates, the first encoder and the second encoder each producing a respective plurality of parity bits for each information bit; puncturing the respective plurality of parity bits at each encoder with a higher rate best puncturing patterns; and puncturing the respective plurality of parity bits at each encoder with a lower rate best puncturing pattern. In a variation, the best rate 1/2 constituent code represents a concatenation of polynomials $1+D^2+D^3$ (octal 13) and $1+D+D^3$ (octal 15), D data bit. A Turbo Encoder is provided which has hardware to implement the method.